

Přehled

Informace o produktu

**40A-GF-4.0-92116900024**

40A silver gold female pins, Adapter wire specification 4.0mm²

Výhoda produktu

- ✓ High-precision turning process, stable and reliable products;
- ✓ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ✓ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certifikace výrobku

Technická data

Tabulka produktů

3D model

☐

Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	4.0mm²
Conductor cross sections(AWG)	12AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	9.6mm
working life-mating cycles	≥500

Příloha

Obchodní data

číslo objednávky	92116900024
Balící jednotka	100
Minimální množství pro objednání	100
Hmotnost výrobku (bez obalu)	2.701