

Přehled

Informace o produktu



16A-SM-0.37-92116900089

16A silver plating male pins, Adapter wire specification 0.37mm²

Výhoda produktu

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certifikace výrobku

Technická data

Tabulka produktů

3D model

□

Marking

classification	Contact
Series	16A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	0.37mm²
Conductor cross sections(AWG)	22AWG
Working current	≤16A
Contact resistance	≤1mΩ
Plating Thickness	≥2μm
Temperature range	-40℃~+125℃
Strip length	7.5mm
working life-mating cycles	≥500

Příloha

Obchodní data

číslo objednávky	92116900089
Balící jednotka	100
Minimální množství pro objednání	100
Hmotnost výrobku (bez obalu)	1.57