

Přehled

Informace o produktu

**D16A-SF-1L-CV-M25-21010000257**

16A Lower base, single buckle, back cover, side entry, M25 Thread hole, Wear protective cover

Výhoda produktu

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

Certifikace výrobku

Technická data

Tabulka produktů

3D model



Marking

classification	Upper Housing/base
Series	A
Type	Surface mount base
Description	With plastic dust cover
Specification	Low structure

versions

Dimension	16A
locking Category	Single lock
Thread specification	1x M25

Material characteristics

Flammability rating	V-0
RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (seal)	NBR
Material (lock catch)	Zinc plated

Technical specification

Limiting temperatures	-40℃~+125℃
IP class	IP65

Příloha

Obchodní data

číslo objednávky	21010000257
Balící jednotka	100
Minimální množství pro objednání	1
Hmotnost výrobku (bez obalu)	226.5