

## Přehled

### Informace o produktu



**D48B-SE-2g-M50-21010000516**

48BHoods,double levers,side entry,M50 Thread hole

### Výhoda produktu

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

### Certifikace výrobku

## Technická data

### Tabulka produktů

### 3D model

□

### Marking

|                |                    |
|----------------|--------------------|
| classification | Upper Housing/base |
| Series         | B                  |
| Type           | Top housing        |
| Specification  | High structure     |

### versions

|                      |             |
|----------------------|-------------|
| Dimension            | 48B         |
| locking Category     | Single lock |
| Wiring method        | Side entry  |
| Thread specification | 1x M50      |

### Material characteristics

|                               |                          |
|-------------------------------|--------------------------|
| RoHS                          | conform                  |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base)  | spray                    |
| Color (upper housing/base)    | Grey (RAL 7037)          |

#### Technical specification

|                       |              |
|-----------------------|--------------|
| Limiting temperatures | -40°C~+125°C |
| IP class              | IP65         |

#### Příloha

#### Obchodní data

|                                  |             |
|----------------------------------|-------------|
| číslo objednávky                 | 21010000516 |
| Balící jednotka                  | 100         |
| Minimální množství pro objednání | 1           |
| Hmotnost výrobku (bez obalu)     | 740         |