

Přehled

Informace o produktu



DD-007-FC-21020000107

Heavy-duty insert, Number of contacts: 7+PE, Dimension: 3A, Rated voltage : 250V, Rated current: 10A, Female insert, Crimping connector

Výhoda produktu

- ☒ Crimping connection technology, high wiring efficiency
- ☒ Suitable for vibration occasions;
- ☒ The wiring harness can be pre-installed;
- ☒ Choose contacts with different wire diameters and coatings;
- ☒ High-density pins, saving installation space;
- ☒ With grounding protection.

Certifikace výrobku



Technická data

Tabulka produktů

3D model

☐

Marking

classification	Insert
Series	DD

versions

Connection method	Crimping connection
Female/Male	Female
Dimension	3A
Number of positions	7

PE Contacts	Yes
-------------	-----

Material characteristics

Material (insert)	Polycarbonate (PC)
Material (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	250V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	6-8mm
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessories

Crimping tool Removal tool	/
----------------------------	---

Obchodní data

číslo objednávky	21020000107
Balící jednotka	100
Minimální množství pro objednání	5
Hmotnost výrobku (bez obalu)	8.19