

Přehled

Informace o produktu



PC6-11010000092

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 800 V, Rated current: 41 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 6 mm², AWG: 24 - 8, Width: 8.2 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Výhoda produktu

- ☒ Screw connection technology, reliable connection;
- ☒ Equipped with fixed parts and bridge parts, circuit connection test is more flexible;
- ☒ Copper alloy material, good corrosion resistance;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Certifikace výrobku



Technická data

Tabulka produktů

3D model

□

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	0.2-4mm ²
Strip length	8~9mm
Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~6mm ²
Conductor cross section solid AWG	24~8

screw thread	M3
Tightening torque	0.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	800V
Rated current (III / 3)	41A
Rated surge voltage	8KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	47.25mm
End plate width	1.6mm
NS 35/15 Height	54.75mm
length	42.5mm
width	8.2mm
Height	46mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA

Flame retardant grade, in line with UL 94

V0

Příloha

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Fixed bridge	FBIXX-8
Insertion bridge	EB2-8 / EB3-8 / EB10-8
End cover	D-PC2.5
Separating disk	TS-K
Partition plate	ATP-PC

Marker

Top marker	/
Marker	ZB8
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB8
Marker cards	DBE-1

Accessories

End cover	D-PC2.5
Grouping Partition plate	TS-K
Partition plate	ATP-PC

Bridge	FBIXX-8
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Obchodní data

číslo objednávky	11010000092
Balící jednotka	50
Minimální množství pro objednání	50
Hmotnost výrobku (bez obalu)	13.953