


Přehled

Informace o produktu



DS1.5-QU-PE-11040000076

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 4, Number of potentials: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 30.6 mm, Color: green-yellow, Mounting type: NS 35/7,5, NS 35/15

Výhoda produktu

- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ Optional marker to avoid wire mis-inserting.
- ☑ Equipped with test holes for easy testing of the circuit.

Certifikace výrobku



Technická data

Tabulka produktů

3D model

□

Wiring data

Strip length	8~10mm
Conductor cross section solid	0.14~1.5mm ²
Conductor cross section flexible	0.14~1.5 mm ²
Conductor cross section solid AWG	26~14

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage

6KV

Environmental protection

REACH SVHC

Lead 7439-92-1

RoHS

No excessive harmful substances

Dimension

NS 35/7,5 Height

32.1mm

End plate width

1.5mm

NS 35/15 Height

39.6mm

length

63.2mm

width

3.5mm

Overview

Connection type

In line connection

Number of rows

1

number of connections

4

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94

V0

Příloha

Marker

Top marker

ZB3.5 / ZS3.5

Side marker

ZSF3.5

Marker support

DTH3.5-25x3.5 / DTH3.5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.4x2.5
Bridge	/
End cover	D-DS1.5-QU

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Obchodní data

číslo objednávky	11040000076
Balící jednotka	100
Minimální množství pro objednání	100
Hmotnost výrobku (bez obalu)	6.113