

Přehled

Informace o produktu



DS1.5-11040000010

Push-in Din-Rail TB, Rated voltage : 500 V, Rated current: 17.5 A, connector method: Push-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Height: 30.6 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

Výhoda produktu

- ☒ Push-in connection technology, tool-free operation, more convenient and faster;
- ☒ With orange wire button, one word or cross screwdriver can release wire.
- ☒ Equipped with dual-channel bridge wells, circuit connection testing is more flexible.
- ☒ Unique plug-in bridge, high circuit connection efficiency.
- ☒ Optional marker to avoid wire mis-inserting.
- ☒ Equipped with test holes for easy testing of the circuit.

Certifikace výrobku



Technická data

Tabulka produktů

3D model

□

Wiring data

Strip length	8~10mm
Conductor cross section solid	0.14~1.5mm ²
Conductor cross section flexible	0.14~1.5 mm ²
Conductor cross section solid AWG	26~14

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
---------------------------------	---

Relative humidity (storage/transport)	25%~75%
---------------------------------------	---------

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	17.5A
Rated surge voltage	6KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	32.1mm
End plate width	1.5mm
NS 35/15 Height	39.6mm
length	45mm
width	3.5mm

Overview

Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Příloha

Marker

Top marker	ZB3.5 / ZS3.5
------------	---------------

Side marker	ZSF3.5
Marker support	DTH3.5-25x3.5 / DTH3.5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.4x2.5
Bridge	DFBXX-3.5
End cover	D-DS1.5

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Obchodní data

číslo objednávky	11040000010
Balící jednotka	100
Minimální množství pro objednání	100
Hmotnost výrobku (bez obalu)	3.05