


## Přehled

### Informace o produktu



## DG24-4-12060000031

Double-layer barrier terminal blocks, Rated current: 8A. Rated voltage (UL) : 300V, Cross section: 24~14AWG, pitch: 7.62mm, Color: gray, Contact surface: Tin

### Výhoda produktu

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Used in industrial control field to save equipment installation space

### Certifikace výrobku

## Technická data

### Tabulka produktů

### 3D model

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

AWG

22~14AWG

Torque

0.5N.m

### Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

8A

Rated current (D)

8A

### Item properties

|                      |                              |
|----------------------|------------------------------|
| Type of installation | PCB welding                  |
| Pin arrangement      | Double-row of misalignment   |
| Connection method    | Screw connection             |
| Screwdriver          | slotted-phillips screwdriver |
| screw thread         | M3                           |
| Pitch                | 7.62mm                       |
| Number of potentials | 12                           |
| Pluggable or not     | no                           |
| Number of rows       | 2                            |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | Copper alloy              |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PBT                       |
| Insulating material group   | IIIa                      |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |        |
|--------------------|--------|
| Test Specification | UL1059 |
|--------------------|--------|

Environmental data

|                                 |             |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~125°C |
|---------------------------------|-------------|

Příloha

Accessories

|  |  |
|--|--|
|  |  |
|--|--|

Obchodní data

|                                     |             |
|-------------------------------------|-------------|
| číslo objednávky                    | 12060000031 |
| Balící jednotka                     | 60          |
| Minimální množství pro<br>objednání | /           |
| Hmotnost výrobku (bez<br>obalu)     | 33.8        |