

Přehled

Informace o produktu

**DGK12-002-13030000004**

Building electronic housing ,length :71.6mm,DIN rail housing ,Can be used in distribution box comply with DIN 43880 standard , Upper housing with vent , IP class:IP20.

Výhoda produktu

- ☒ Modern design
- ☒ flexible PCB connection
- ☒ high-efficiency DIN rail connector is optional
- ☒ Support Wall-mounted installation and distribution power box installation in accordance with DIN 43880 standards

Certifikace výrobku

Technická data

Tabulka produktů

3D model



Dimensions

width	71.6mm
length	89.7mm
Height	60.7mm
Depth from top edge of DIN rail	54.7mm

PCB data

Number of PCB holders	17 (Upper cover 8+Base 9)
PCB thickness	1.8mm
Installation location	Vertical &horizontal(DIN rail)
PCBType of installation	Latching

Item properties

IP class	IP20
Connection levels	1(Both sides)
with ventilation openings	Yes
Maximum connection	44 (pitch : 2.5 mm);24 (pitch : 5 mm),16 (pitch : 7.5 mm)

Material data

color	Upper housing: light gray bottom housing: black
Material	PC
Flammability rating	V2

Environmental data

Ambient temperature (assembly)	-5°C ~ +100°C
Ambient temperature (operation)	-40°C ~ +110°C
Ambient temperature (storage / transport)	-40°C ~ +70°C

Příloha

Accessories

--	--

Obchodní data

číslo objednávky	13030000004
Balící jednotka	84
Minimální množství pro objednání	84
Hmotnost výrobku (bez obalu)	59.5