

Přehled

Informace o produktu

**MIL cable-DX210-2S-500-00A(H)-23040000007**

MIL cable,connector1:IDC/MIL female connector (1×20 Core,90° output) ,connector2:IDC/MIL female connector (1×20 Core,90° output)

Výhoda produktu

- ☑The cable is soft and has good bending resistance
- ☑Prefabricated connector, beautiful appearance
- ☑ Provide single-ended and double-ended cables
- ☑ Save wiring time, and can achieve fast wiring with the company's interface module

Certifikace výrobku

Technická data

Tabulka produktů

3D model

□

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC
-----------------------------------	-------

Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	6.1mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	20
spacing	2.54mm
Exit angle	90°

Connection data 2

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	20
Exit angle	90°
spacing	2.54mm

Overview

Single wire, number of twisted wires	20
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC
Outer sheath,color	black

Příloha

Obchodní data	
číslo objednávky	23040000007
Balící jednotka	1
Minimální množství pro objednání	10
Hmotnost výrobku (bez obalu)	50