

Přehled

Informace o produktu



MIL cable-DX210-1DS-500-00A(H)-23040000004

MIL cable,connector1:IDC/MIL female connector (1×10 Core,180° output) ,connector2:multi-Core Cable

Výhoda produktu

- ☒ The cable is soft and has good bending resistance
- ☒ Prefabricated connector, beautiful appearance
- ☒ Provide single-ended and double-ended cables
- ☒ Save wiring time, and can achieve fast wiring with the company's interface module

Certifikace výrobku

Technická data

Tabulka produktů

3D model

□

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
---------------------------------	------------------

Ambient temperature (storage / transport)	-20 °C ... 80 °C
---	------------------

Standards/Regulations

Flame retardant	UL VW-1
-----------------	---------

Oil resistance	Oil resistant
----------------	---------------

Gasoline resistance	≤246Ω/KM
---------------------	----------

Connection meets standards	UL 758
----------------------------	--------

Technical data

Maximum allowable working voltage	30VDC
-----------------------------------	-------

Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	5.0mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	Control system side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	10
spacing	2.54mm
Exit angle	180°

Connection data 2

Connection name	On-site side
Connection method	Multi-core wire
Connection volume	1
Number of digits	10
spacing	2.54mm

Overview

Single wire, number of twisted wires	10
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC
Outer sheath,color	black

Příloha

Obchodní data	
číslo objednávky	23040000004
Balící jednotka	1
Minimální množství pro objednání	10
Hmotnost výrobku (bez obalu)	50