

## Přehled

### Informace o produktu



## DGP95-10090000017

Through-wall terminal blocks, Rated current: 232A. Rated voltage (III/3) : 1000V, Width: 25.0mm, Color: gray, Contact surface : Tin

### Výhoda produktu

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

### Certifikace výrobku

## Technická data

### Tabulka produktů

### 3D model

□

### Connection capacity

|                                  |                      |
|----------------------------------|----------------------|
| Conductor cross section solid    | 25~95mm <sup>2</sup> |
| Conductor cross section flexible | 25~95mm <sup>2</sup> |
| AWG                              | 4~4/0AWG             |
| Strip length                     | 27mm                 |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 600V |
| Rated voltage (C) | 600V |
| Rated voltage (D) | 600V |
| Rated current (B) | 230A |
| Rated current (D) | 5A   |

|                   |      |
|-------------------|------|
| Rated current (C) | 230A |
|-------------------|------|

Electrical parameters IEC

|                            |       |
|----------------------------|-------|
| Rated current(III/3)       | 1000V |
| Rated current              | 1000V |
|                            | 232A  |
| Rated surge voltage(III/3) | 8KV   |

Item properties

|                      |                     |
|----------------------|---------------------|
| Type of installation | panel               |
| Connection method    | Screw connection    |
| Screwdriver          | Hexagon screwdriver |
| screw thread         | M8                  |
| Pitch                | 25mm                |
| Number of potentials | 1                   |
| Pluggable or not     | no                  |
| Number of rows       | 1                   |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |                 |
|--------------------|-----------------|
| Test Specification | IEC60947/UL1059 |
|--------------------|-----------------|

Environmental data

Ambient temperature (operation)

-40°C~105°C

## Příloha

### Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

### Tool

Operating tool

/

Screwdriver

/

## Obchodní data

číslo objednávky

10090000017

Balící jednotka

10

Minimální množství pro  
objednání

30

Hmotnost výrobku (bez  
obalu)

293