

Přehled

Informace o produktu



DG245-7.62-10060001320

PCB spring terminal blocks, Rated current: 17A. Rated voltage
(III/2) : 750V, pitch: 7.62mm, Color: gray, Contact surface : Tin

Výhoda produktu

- ☒ Cage clamp connection technology, fast wiring
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

Certifikace výrobku



Technická data

Tabulka produktů

3D model

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~2.5mm²

Conductor cross section flexible

0.2~2.5mm²

AWG

28~12AWG

Strip length

6mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	750V
Rated current	17A
Rated current(III/2)	750V
Rated power frequency voltage(1min)	3KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	7.62mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Příloha

Accessories

Coding strip	/
--------------	---

Bridge	/
--------	---

Marking strip	/
---------------	---

Others	/
--------	---

Tool

Operating tool	/
----------------	---

Screwdriver	/
-------------	---

Obchodní data

číslo objednávky	10060001320
------------------	-------------

Balící jednotka	1750
-----------------	------

Minimální množství pro objednání	30
-------------------------------------	----

Hmotnost výrobku (bez obalu)	1.3
---------------------------------	-----