


Přehled

Informace o produktu



DG140V-5.0-10030003081

PCB terminal blocks, Rated current: 24A, Rated voltage (III/2) 630V, Cross section: 2.5mm², pitch: 5.0mm, connector method: Quick plug connector, Color: Orange, Contact surface: Tin

Výhoda produktu

- ☒ Quick plug-in connection, fast wiring
- ☒ The plug direction is perpendicular to PCB
- ☒ Universal installation method to ensure a high degree of flexibility in device design

Certifikace výrobku



Technická data

Tabulka produktů

3D model

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.5~2.5mm²

Conductor cross section flexible

0.5~2.5mm²

AWG

26~14AWG

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	630V
Rated current	24A
Rated current(III/2)	630V
Rated power frequency voltage(1min)	3KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Quick connection
Pitch	5mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-2

Mechanical tests

Test Specification	IEC60998
--------------------	----------

Environmental data

Ambient temperature (operation)	-40°C~85°C
---------------------------------	------------

Příloha

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Obchodní data

číslo objednávky	10030003081
Balící jednotka	#N/A
Minimální množství pro objednání	30
Hmotnost výrobku (bez obalu)	#N/A