

Přehled

Informace o produktu



2EDG-UDB-5.08-10010002836

Pluggable terminal blocks, Rated current: 12A. Rated voltage
(III/2) : 320V, pitch: 5.08mm, Color: green, Contact surface : Tin

Výhoda produktu

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Din rail installation, suitable for various situations

Certifikace výrobku



Technická data

Tabulka produktů

3D model

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~2.5mm²

Conductor cross section flexible

0.2~2.5mm²

AWG

28~12AWG

Torque

0.6N.m

Strip length

7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current(III/3)	250V
Rated current	12A
Rated current(III/2)	320V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Type of installation	Rail mounting
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Příloha

Tool

Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	/

Accessories

Coding strip	2EDG-PWP
Bridge	/
Marking strip	/
Others	/

Obchodní data

číslo objednávky	10010002836
Balící jednotka	315

Minimální množství pro objednání	30
Hmotnost výrobku (bez obalu)	8.73