

## Přehled

## Informace o produktu

**RM-EBBM-2003-M-25060000001**

Quick in-line plug, rated current 20A; rated voltage 110V DC; withstand voltage 500V AC; insulation resistance > 100MΩ; protection class IP67; ; Salt spray resistance 72h; Flame retardant grade UL94-V0; Environmental RoHS. Color: Housing - Black

## Výhoda produktu

- ☒ Quick direct plug connection
- ☒ Auditory and visual feedback when plugged in place
- ☒ High plug life
- ☒ Beautiful appearance, more ergonomic design

## Certifikace výrobku

**RoHS**

## Technická data

## Tabulka produktů

## 3D model

□

## Marking

| classification | Insert |
|----------------|--------|
| Series         | DD     |
|                | DE     |
|                | DM     |

## versions

| Connection method | Crimping connection |
|-------------------|---------------------|
| Female/Male       | Male                |

|                     |     |
|---------------------|-----|
| Dimension           | 3A  |
|                     | 10A |
|                     | 6B  |
|                     | 10B |
|                     | 16B |
|                     | 24B |
|                     | 32B |
|                     | 48B |
| Number of positions | 4   |
|                     | 2   |

|         |
|---------|
| Příloha |
|         |

|                                  |             |
|----------------------------------|-------------|
| Obchodní data                    |             |
| číslo objednávky                 | 25060000001 |
| Balící jednotka                  |             |
| Minimální množství pro objednání |             |
| Hmotnost výrobku (bez obalu)     |             |