


## Přehled

## Informace o produktu

**DG75-A-12050000239**

Up and down transfer terminal, nominal current: 75A. Rated voltage (UL): 600V, rated cross section: 22~4AWG, pitch: 16mm, color: black, contact surface: tin

## Výhoda produktu

- ☒ Screw connection for worldwide use
- ☒ Barrier wiring structure, stable and reliable connection
- ☒ It can meet the high current electrical connection at the power end

## Certifikace výrobku



## Technická data

## Tabulka produktů

## 3D model

[□](#)

## Wiring capacity

torque

5N.m

## Connection capacity

AWG

22~4AWG

## Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated voltage (D)

600V

Rated current (B)

75A

|                   |     |
|-------------------|-----|
| Rated current (D) | 5A  |
| Rated current (C) | 75A |

Item properties

|                      |                               |
|----------------------|-------------------------------|
| Type of installation | panel                         |
| Pin arrangement      | Single row in a straight line |
| Connection method    | Screw connection              |
| Screwdriver          | Phillips screwdriver          |
| screw thread         | M6                            |
| Pitch                | 16mm                          |
| Number of potentials | 1                             |
| Pluggable or not     | no                            |
| Number of rows       | 1                             |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | Nickel plating            |
| Insulation Materials        | PBT                       |
| Insulating material group   | IIIa                      |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |        |
|--------------------|--------|
| Test Specification | UL1059 |
|--------------------|--------|

Environmental data

|                                 |             |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~120°C |
|---------------------------------|-------------|

## Obchodní data

|                                     |             |
|-------------------------------------|-------------|
| číslo objednávky                    | 12050000239 |
| Balící jednotka                     | 45          |
| Minimální množství pro<br>objednání | /           |
| Hmotnost výrobku (bez<br>obalu)     | 66          |