


## Přehled

### Informace o produktu



### WS2.5-DB-21A(H)-11030000134

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 24 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 28 - 14, Width: 6 mm, Color: gray, Mounting type: Panel installation

### Výhoda produktu

- ☒ spring-cage connection technology, good anti-vibration performance;
- ☒ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☒ Panel installation, no need to install on the guide rail;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

### Certifikace výrobku



## Technická data

### Tabulka produktů

### 3D model

□

### Wiring data

|                                   |                        |
|-----------------------------------|------------------------|
| Strip length                      | 8~9mm                  |
| Conductor cross section solid     | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section solid AWG | 28~14                  |

### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 24A  |
| Rated surge voltage     | 8KV  |

Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

Dimension

|                 |       |
|-----------------|-------|
| End plate width | 2.5mm |
| length          | 28mm  |
| width           | 6mm   |
| Height          | 18mm  |

Overview

|                                           |                             |
|-------------------------------------------|-----------------------------|
| Connection type                           | Pull back spring connection |
| Number of rows                            | 1                           |
| number of connections                     | 2                           |
| Open-end side panels                      | Yes                         |
| Insulation Materials                      | PA                          |
| Flame retardant grade, in line with UL 94 | V0                          |

Příloha

Marker

|                |      |
|----------------|------|
| Top marker     | /    |
| Side marker    | DEK6 |
| Marker support | /    |

|               |   |
|---------------|---|
| Warning cover | / |
|---------------|---|

#### Accessories

|                                                    |                   |
|----------------------------------------------------|-------------------|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5           |
| Adjacent jumper (2P)                               | /                 |
| Alternate jumper (2P)                              | /                 |
| Staggered jumper (2P)                              | /                 |
| End cover                                          | D-WS2.5-DB-12A(H) |

#### Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

#### Obchodní data

|                                  |             |
|----------------------------------|-------------|
| číslo objednávky                 | 11030000134 |
| Balící jednotka                  | 200         |
| Minimální množství pro objednání | 200         |
| Hmotnost výrobku (bez obalu)     | 2.388       |