

Přehled

Informace o produktu



9EDGRB-HC-5.0-DA-10030010658

Pluggable terminal blocks, Rated current: 20A. Rated voltage (III/3) : 500V, pitch: 5.0mm, Color: black, Contact surface : Tin

Výhoda produktu

- ☒ Supporting 9EDGKD-HC plug
- ☒ Insert and remove direction parallel to PCB
- ☒ Fixed foot structure, PCB installation is more firm

Certifikace výrobku



Technická data

Tabulka produktů

3D model

□

Packaging information

Type of packaging

box-packed

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

20A

Rated current (D)

10A

Electrical parameters IEC

Rated voltage

500V

Rated current(III/3)	500V
Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Push-in spring connection
Pitch	5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Glow Wire Flammability Index GWFI	850
Shell color	Black
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Příloha

Tool

Screwdriver

/

Operating tool

/

Accessories

Coding strip

2EDG-PWP-01A(H)

Bridge

/

Marking strip

/

Others

/

Obchodní data

číslo objednávky

10030010658

Balicí jednotka

1600

Minimální množství pro
objednáníHmotnost výrobku (bez
obalu)

1.6