

Přehled

Informace o produktu



2EDGRHCM-5.08-10030010556

Pluggable terminal blocks, Rated current: 8A. Rated voltage (III/2) : 400V, pitch: 5.08mm, Color: black, Contact surface : Tin

Výhoda produktu

- ☒ Double-layer compact design
- ☒ Suitable for wave soldering and reflow welding

Certifikace výrobku



Technická data

Tabulka produktů

3D model

□

Packaging information

Type of packaging

bag packaging

Processing notes

Process

Reflow soldering/wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

10A

Rated current (D)

10A

Electrical parameters IEC

Rated voltage	400V
Rated current(III/3)	250V
Rated current	8A
Rated current(III/2)	400V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
screw thread	M2
Pitch	5.08mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Relative tracking index CTI	250V
Glow Wire Flammability Index GWFI	850
Shell color	Black
Insulating material group	IIIa

Flammability rating	UL94V-0
---------------------	---------

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~120°C
---------------------------------	-------------

Příloha

Tool

Screwdriver	/
-------------	---

Operating tool	/
----------------	---

Accessories

Coding strip	/
--------------	---

Bridge	/
--------	---

Marking strip	/
---------------	---

Others	/
--------	---

Obchodní data

číslo objednávky	10030010556
------------------	-------------

Balící jednotka	990
-----------------	-----

Minimální množství pro objednání	
-------------------------------------	--

Hmotnost výrobku (bez obalu)	3.54
---------------------------------	------